

MicroCFoam Product Availability

MicroCFoam Product Availability																	
Common series for handheld devices	P/RP	PZ-145	PZ-200	PZ-240	PZ-320	PZ-400	PZ-480	PZ-650	A	PZ-145	PZ-200	PZ-240	PZ-400	PZ-480	P/A/AR	PV-100	PV-150
	0.20							P	0.20						0.20		
	0.30	P						P	0.30	A				A	0.30	0.35A/RP	0.35A
	0.40	P							0.40	A					0.40		
	0.50	P/RP	P				P/PB	P	0.50	A/AW	A	A	A	A	0.50	0.48A/0.53A/RP	A/P/RP
	0.60	P					P		0.60					A	0.60		P
	0.70		P/PB	P			P/PB		0.70		A	A	A		0.70		
	0.75	P							0.75						0.75	P	P
	0.80		P				P/2RP/PB		0.80	A				A	0.80		
	1.00	P		P			P/PB		1.00		A			A	1.00	P	P
	1.25		P	P	1.20P/2RP		1.2PB		1.20					A	1.20		
	1.50		P/RP				P/PB/RP		1.50					A	1.50		
	2.00	P	P/RP	P/RP	P		2.2RP/2.5PB		2.00					2.5A	2.00		
	3.00		RP	P/RP			PB		3.00						3.00		
	3.18			RP					3.18						3.18		
4.78			RP					4.78						4.78			
Super thin series	P	PT-240	PT-320	PT-480	PT-500	A/AR	PT-240	PT-320	PT-400	PT-480	PT-500	RP	PS-240	PM-300	PM-400	PH-300	PH-400
	0.08					0.08						0.08					
	0.10		P		P	0.10		A/AR	A/AR	AR	A	0.10			RP		RP
	0.15	P	P			0.15	A/AR	A/AR		A		0.15	RP			RP	RP
	0.18					0.18						0.18		RP		RP	
	0.20		P	P	P	0.20	A/AR	A/AR	A/AR	A/AR	A	0.20				RP	
	0.25					0.25						0.25					RP
	0.30		P			0.30		A/AR				0.30				RP	
Common series for general industry	P/RP	PS-240	PS-320	PS-400	PM-240	PM-320	PM-480	PH-240	PH-320	PH-480	PF-480	Legend: None blank cell represents the standard product. The column heading is formula and density. The row heading is thickness. P PET support. RP With release PET. 2RP Release PET on both side. PB Black PET support. A With adhesive. AR Wlth air release adhesive. 0.83P The accurate thickness is 0.83mm. PET support.					
	0.30								0.25P	P							
	0.50	P								0.43RP/0.5RP							
	0.70	P							P								
	0.80	P	0.83P	RP			RP				RP						
	0.90			RP													
	0.94			P													
	1.00					RP				P/RP	P/RP						
	1.14			RP			RP			RP							
	1.20			P							P						
	1.50										P/RP						
	1.57		RP			RP			RP								
	1.63		P														
	2.00					RP					P/RP						
	2.40		P/RP			RP			2.36RP		2.5P						
3.18		RP		3.0RP	RP		3.0/3.5RP	RP		3.0RP							
4.78	RP	RP		RP			4.0/4.5/4.78RP										
6.35	RP			RP			6.0RP										